



US006679130B2

(12) **United States Patent**
Hajduk et al.

(10) **Patent No.:** **US 6,679,130 B2**
(45) **Date of Patent:** **Jan. 20, 2004**

(54) **INSTRUMENT FOR HIGH THROUGHPUT MEASUREMENT OF MATERIAL PHYSICAL PROPERTIES OF A PLURALITY OF SAMPLES**

3,713,328 A 1/1973 Aritomi
3,798,960 A 3/1974 Glass

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Damian Hajduk**, San Jose, CA (US);
Eric Carlson, Palo Alto, CA (US); **J. Christopher Freitag**, Santa Clara, CA (US); **Oleg Kosolov**, Cupertino, CA (US)

CA 2112792 * 1/1994 G01B/7/34
EP 0 317 356 A2 5/1989

(List continued on next page.)

OTHER PUBLICATIONS

(73) Assignee: **Symyx Technologies, Inc.**, Santa Clara, CA (US)

Bowlt, C., "A Simple Capillary Viscometer" Physics Education, Mar. 1975, vol. 10, No. 2, pp. 102-103.

(List continued on next page.)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

Primary Examiner—Thomas P. Noland
(74) *Attorney, Agent, or Firm*—Dobrusin & Thennisch PC

(57) **ABSTRACT**

(21) Appl. No.: **09/779,148**

(22) Filed: **Feb. 8, 2001**

(65) **Prior Publication Data**

US 2002/0023507 A1 Feb. 28, 2002

Related U.S. Application Data

(62) Division of application No. 09/580,024, filed on May 26, 2000.

(51) **Int. Cl.**⁷ **G01N 3/00**; G01N 3/08;
G01N 3/24; G01N 11/04; G01N 3/02

(52) **U.S. Cl.** **73/866**; 73/54.02; 73/81;
73/794; 73/819

(58) **Field of Search** 73/866, 865.6,
73/54.02, 54.36, 54.37, 54.38, 54.43, 81,
788, 794, 795, 1, 799, 819, 822, 847, 78,
104, 105

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,870,412 A 8/1932 Kennedy
3,071,961 A 1/1963 Heigl et al.
3,675,475 A 7/1972 Weinstein 73/89

An apparatus and method for screening combinatorial libraries of materials by measuring the response of individual library members to mechanical perturbations is described. The apparatus generally includes a sample holder for containing the library members, an array of probes for mechanically perturbing individual library members, and an array of sensors for measuring the response of each of the library members to the mechanical perturbations. Library members undergoing screening make up a sample array, and individual library members constitute elements of the sample array that are confined to specific locations on the sample holder. During screening, the apparatus mechanically perturbs individual library members by displacing the sample array (sample holder) and the array of probes. Typically, all of the elements of the sample array are perturbed simultaneously, but the apparatus also can also perturb individual or groups of sample array elements sequentially. The flexible apparatus and method can screen libraries of materials based on many different bulk physical properties, including Young's modulus (flexure, uniaxial extension, biaxial compression, and shear); hardness (indentation), failure (stress and strain at failure, toughness), adhesion (tack, loop tack), and flow (viscosity, melt flow indexing, and rheology), among others.

77 Claims, 15 Drawing Sheets

